Bay Bridge Mullen THREE Lightweight Van Body

Standard Features

- Aluminum Sidewall Frame Construction
- 1 1/2" Aluminum I-Beam Sidewall Studs on 16" CTRS
 .032 Exterior Roof Aluminum
- 9MM Birch Luan Sidewall Wall Lining
- .040 Buckrivets Ext. White Sidewall Aluminum
- 13 Gauge Steel Flat Floor Frame
- 13 Gauge Steel Hat Section X-Members on 16" CTRS
- 10 Gauge Steel Rear Floor Frame Sill
- 12 Gauge Steel Rear Door Structure
- Steel ICC Rear Dock Bumper
- LED Clearance, Brake, & Turn Lights
- Complete Body Undercoating
- 3 year Limited Body Warranty
- 1/2" FRP Solid Bulkhead
- 2"x6" Shiplap Dense Pine Floor

- · Roof Bows on 16" Centers
- Extruded .125 Alum. 3" Radius CNR Posts
- Extruded .125 Alum. 3" Radius Roof Rails
- .130 Aluminum Protective Rub Rails
- · Dome Light with Switch
- Rear Mud Flaps

Model Length	Interior Length	Interior Height	Interior Width	Interior Door Width	Interior Door Height	Overall Width	Overall Height
14'	14'	6'6"	92"	86"	72"	96"	122"
14'	14'	7′	92"	86"	78"	96"	128"
14'	14'	7′6″	92"	86"	83"	96"	134"





Pre-production model shown

* Specifications are based on a flat floor with roll up rear door. All measurements are approximate and subject to change. Please contact your sales representative for specific dimensions.



MANUFACTURING, INC.

800.451.6267 · info@baybridgemfg.com

LEARN MORE ONLINE: WWW.BAYBRIDGEMFG.COM





Amerit Fleet Solutions is Mullen's national service and warranty repair provider with over 1,800 highly trained vehicle service technicians across the United States.

DIMENSIONS	S & CAPACITY					
Wheelbase	130 in.					
L×W×H	230×77×88					
GVWR	11,000 lbs.					
Curb Weight	5,684 lbs.					
Max Payload	5,316 lbs.					
Bumper to Back of Cab (BBC)	65.8 in.					
Cab to Axle (CA)	108.3 in.					
Cab to End of Frame (CE)	164.5 in					
Maximum Body Length	14 ft.					
Maximum Body Width	96 in.					
Frame RBM	541,675 (lbft./in.)					
MECHANICAL						
Electric Motor	120 kW					
Battery Capacity	89 kWh					
Range	125 ⁽¹⁾ miles					
Regenerative Braking	Standard					
Level 2 Charging	up to 12kW					
Level 3 DC Charging	up to 78kW					
Drive Type	Rear Wheel Drive (RWD)					
PERFORMANCE						
Horsepower	160 hp					
Torque	235 lbft.					
	65 mph					
Top Speed	00111011					
	INECTIVITY					

EXTERIOR FEATURES:								
Full Size Spare Tire								
Tilt Cab Top/Side Marker Lighting								
INTERIOR FEATURES								
Analog Gauges with Digital Driver Info Center								
Auxiliary Power Outlet								
Digital AM/FM/Bluetooth/USB Port								
High-Definition Back-Up Camera								
7-Inch Infotainment Color Touchscreen								
Dual Storage Glove Box								
Illuminated Entry, Air Conditioning, Sun Visors								
Power Door Locks & Windows								
Cloth Seating Surfaces								
Adjustable Front Head Restraints								
Driver Seat - Manual Fore/Aft with Recline								
Passenger Seat - Bench with Fold Down Back								
Center Seat with Fold Down Workspace								
Center Workspace includes Dual Cupholders/Storage								
SAFETY FEATURES								
Anti-Theft Alarm System								
ABS Braking with Regenerative Braking (ABS)								
Electronic Brake-Force Distribution (EBD)								
Center Console Manual Parking Brake								
Assist Steps and Grab Handles								
Power Steering								
Remote Keyless Entry (2 Key Fobs)								

The Manufacturer's Suggested Retail Price (MSRP) excludes destination freight charge, tax, title, license, dealer fees and optional equipment. Dealer sets final price.

Note: All figures are reference only and Mullen reserves the right to modify any and all information shown, without notification. Options subject to change.

 $(1) \ Combined \ City/Highway \ usage \ with 10 \ percent \ remaining \ battery \ state \ of \ charge. \ Range \ can \ vary \ depending \ on \ conditions \ such \ as \ climate, \ driving \ behavior, \ road \ conditions, \ etc.$

mullencommercial.com 1223